

# Especificaciones



La foto es representativa



## Eaton FRS-R-350

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 350 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series FRS-R fuse
<b>CATALOG NUMBER</b>	FRS-R-350
<b>UPC</b>	051712508520
<b>PRODUCT LENGTH/DEPTH</b>	11.63 in
<b>PRODUCT HEIGHT</b>	2.59 in
<b>PRODUCT WIDTH</b>	2.59 in
<b>PRODUCT WEIGHT</b>	0.00052 lb
<b>COMPLIANCES</b>	CE Marked



Powering Business Worldwide

## Especificaciones del producto

<b>AMPERAGE RATING</b>	350 A
<b>NUMBER OF ELEMENTS</b>	Dual
<b>CLASS</b>	Class RK5
<b>INTERRUPT RATING</b>	20 kAIC at 300 Vdc 200 kAIC at 600 Vac
<b>FUSE INDICATOR</b>	Non-indicating
<b>CONNECTION</b>	Blade end x blade end
<b>RESPONSE TIME</b>	10 sec at 500%
<b>PACKAGING TYPE</b>	Standard
<b>VOLTAGE RATING</b>	600 Vac, 300 Vdc
<b>TYPE</b>	Current-limiting time-delay fuse
<b>APPLICATION</b>	Combination starters, motor control centers, machinery disconnects, power panelboards

## Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



**Eaton Corporation plc** Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

