







# Product comparison between Linksys SE3005, SE3008, SE3016, SE3024, SE3005 v2, and SE3008 v2

The Linksys SE3005, SE3008, SE3016, and SE3024 are unmanaged switches that offer a quick and easy solution to extend your office network with a plug-and-play installation. It has built-in full-duplex 10/100/1000 switch to connect your wired ethernet devices together at up to gigabit speeds.

Features	SE3005	SE3005 v2	SE3008	SE3008 v2	SE3016	SE3024
Product Image						
LAN Ports (Auto-Sensing)	5- 10/100/1000	5- 10/100/1000	8- 10/100/1000	8- 10/100/1000	16- 10/100/1000	24- 10/100/1000
Standard	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.3az
QoS	802.1p	802.1p	802.1p	802.1p	802.1p	802.1p
LED	System (Blue)	System (Blue) Link / Act	System (Blue)	System (Blue) Link / Act	System (Blue)	System (Blue)



	Link / Act (Green)	(Green, Orange)	Link / Act (Green)	(Green, Orange)	Link / Act (Green)	Link / Act (Green)
Power	5 Volts, 1 Ampere	12 Volts, 0.5 Ampere	5 Volts, 1 Ampere	12 Volts, 0.5 Ampere	Power cord only (Internal AC 100 - 240 V ~ 50 / 60 Hz)	Power cord only (Internal AC 100 - 240 V ~ 50 / 60 Hz)
Dimensions (W x D x H)	121 x 75 x 26 mm	120 x 88 x 26 mm	154 x 85 x 26 mm	168 x 90 x 26 mm	215.5 x 133 x 42 mm	441 x 131 x 44 mm
Mountable	Desktop	Desktop	Desktop	Desktop	Rack	Rack
Environmental	Operating Temperature 32 to 104 °F (0 to 40 °C)	Operating Temperature 32 to 104 °F (0 to 40 °C)	Operating Temperature 32 to 104 °F (0 to 40 °C)	Operating Temperature 32 to 104 °F (0 to 40 °C)	Operating Temperature 32 to 104 °F (0 to 40 °C)	Operating Temperature 32 to 104 °F (0 to 40 °C)
	Storage Temperature -4 to 158 °F (-20 to 70 °C)	Storage Temperature -4 to 158 °F (-20 to 70 °C)	Storage Temperature -4 to 158 °F (-20 to 70 °C)	Storage Temperature -4 to 158 °F (-20 to 70 °C)	Storage Temperature -4 to 158 °F (-20 to 70 °C)	Storage Temperature -4 to 158 °F (-20 to 70 °C)
	Operating Humidity 10 to 90%, non- condensing	Operating Humidity 10 to 90%, non- condensing	Operating Humidity 10 to 90%, non- condensing	Operating Humidity 10 to 90%, non- condensing	Operating Humidity 10 to 90%, non- condensing	Operating Humidity 10 to 90%, non- condensing
	Storage Humidity 5 to 90%, non- condensing	Storage Humidity 5 to 90%, non- condensing	Storage Humidity 5 to 90%, non- condensing	Storage Humidity 5 to 90%, non- condensing	Storage Humidity 5 to 90%, non- condensing	Storage Humidity 5 to 90%, non- condensing



LED	Color	Activity	Description
Power / System	Blue	Off	Power Off
		On	Power on and device ready
Ethernet	Green	Off	No Ethernet connection
		On	Ethernet is connected
		Blinking	Ethernet traffic
	Orange	On	Ethernet is connected (100/10 Mbps connection)
		Blinking	Ethernet traffic

## Related Articles:

[Getting to know the Linksys SE3005 5-Port Gigabit Ethernet Switch](#)

[Linksys SE3008 8-Port Gigabit Ethernet Switch Frequently Asked Questions](#)

Support

Contact Us

Tech Briefs

Linksys

FAQs

Press



© Linksys Holdings, Inc. 2026. All rights reserved. [Privacy & Security](#) [Accessibility](#) [Documentation](#) [Terms of Use](#)  
[Modern Slavery Act](#) [PSTI Compliance](#)

